

CE certified Aluminium/wood sliding sash windows:

Supplier to be Marvin Architectural Ltd,

Stephen St. Dunlavin, Co. Wicklow 045 401000;

Product referral; Clad Ultimate Double Hung; Species Pinus Ponderosa, knot and defect free;

External Aluminium sash & frame to be extruded aluminium 1.4mm min;

Exterior Paint finish 2 coats finish system using Kynar AAMA 2605:

Double –Vac wood *preservative* to give 60 years services life.

Surface mounted Open style crescent sash lock with tilt in cleaning capacity:

Block & Tackle balance system:

Continuous leaf weather-stripping at head jamb; dual bulb at checkrail; weatherstrip and bottom rail;

Jamb extensions and shutters finishes available, contact Marvin Architectural for details;

Insect and combination storm screens available, contact Marvin Architectural for details;

Glazing bars, available in simulated divided light with/without spacer bars, grilles between glass, interior grille option, coloured perimeter and spacer bar options,

Glazing bar widths are available in 16mm, 22mm, 28mm, 61mm and for custom option availability contact Marvin Architectural for details.

Soft coast low E 272 with warm edge space,

Glazing to conform to EN1279;

This window product is to conform to EN 14351-1 :2006

To Meet or exceed on Air permeability EN 12207, class 3

Water-tightness EN 12208, class 7A,

Resistance to wind load EN 12210, class B3,

Light Transmittance, 0.72.

Solar Heat Gain, 0.49.

Thermal Transmittance between 1.2 & 1.8,